

CLAIMS

The invention claimed is:

1. A device for preventing unintentional removal of a slot in an end of a guitar strap from an engaged guitar strap peg of a guitar, wherein the engaged guitar strap peg of the guitar has a neck that extends from the guitar, to an end, and has a contour and a thickness, and wherein the engaged guitar strap peg of the guitar further has a head that extends radially outwardly from the end of the neck thereof, said device comprising a body for positioning on the guitar strap peg of the guitar, outboard of the guitar strap of said guitar, and for preventing unintentional removal of the slot in the end of the guitar strap from the engaged guitar strap peg of the guitar.
2. The device as defined in claim 1, wherein said body is disk-shaped.
3. The device as defined in claim 1, wherein said body has:
 - a) a center;
 - b) a periphery;
 - c) a first surface that is circular-shaped and is for abutting against the head of the engaged guitar strap peg of the guitar; and
 - d) a second surface that is circular-shaped, disposed oppositely to said first surface thereof, and is for abutting against, and overpassing, the slot in the end of the guitar strap of the guitar.
4. The device as defined in claim 3, wherein said body further has a throughbore that is circular-shaped, has a diameter, a perimeter,

and a chord with a length and ends that intersect said perimeter of said throughbore in said body.

5. The device as defined in claim 4, wherein said diameter of said throughbore in said body is for being slightly greater than the thickness of the engaged guitar strap peg of the guitar.
6. The device as defined in claim 4, wherein said length of said chord of said throughbore in said body relative to the thickness of the engaged guitar strap peg of the guitar is such so as to allow the engaged guitar strap peg of the guitar to slide snugly therepast.
7. The device as defined in claim 4, wherein said throughbore in said body extends through said center thereof, from said first surface thereof, to said second surface thereof, and is for receiving the neck of the engaged guitar strap peg of the guitar.
8. The device as defined in claim 4, wherein said body further has a throughslot that communicates with said throughbore therein and said periphery thereof, and is for allowing the neck of the engaged guitar strap peg of the guitar to slide therein, and into said throughbore in said body, and when in said throughbore in said body, said first surface of said body is wedged against the head of the engaged guitar strap peg of the guitar, and said second surface of said body wedges the guitar strap of the guitar against the guitar, and when doing so, prevents the slot in the end of the guitar strap of the guitar from escaping past the head of the engaged guitar strap peg of the guitar, and in doing so, prevents the guitar strap of the guitar from being unintentionally removed from the engaged guitar strap peg of the guitar.

097735 04904

- 1 9. The device as defined in claim 8, wherein said throughslot in said
2 body is defined by a pair of edges that equidistantly straddle a
3 radius of said body, are straight, oppose each other, and extend
4 radially outwardly from said pair of ends of said chord of said
5 throughbore in said body, respectively, to said periphery of said
6 body, where they are rounded for facilitating original engagement
7 with the engaged guitar strap peg of the guitar and for eliminating
8 guitar strap peg damaging sharp points.
- 9 10. The device as defined in claim 3, wherein said perimeter of said
10 throughbore in said body is slightly beveled completely therearound,
11 on said first surface of said body, for conforming to the contour of
12 the neck leg 20 of the engaged guitar strap peg of the guitar so as
13 to provide a snugger fit and for eliminating a guitar strap peg
14 damaging sharp edge.
- 15 11. The device as defined in claim 9, wherein said throughslot in said
16 body is rectangular-shaped, and said pair of edges thereof are
17 parallel to each other and spaced-apart from each other a distance
18 for allowing the engaged guitar strap peg of the guitar to slide
19 snugly therebetween, and as a result thereof, allows said device to
20 engage the engaged guitar strap peg of the guitar when the engaged
21 guitar strap peg of the guitar is not in said throughbore in said
22 body so as to prevent said device from jumping off the engaged
23 guitar strap peg of the guitar.
- 24 12. The device as defined in claim 9, wherein said throughslot in said
25 body is isosceles-triangular-shaped.
- 26 13. The device as defined in claim 12, wherein said pair of edges of
27 said throughslot in said body divergingly straddle said radius of
28 said body, and extend radially outwardly from said ends of said

1
2
3
4

chord of said throughbore in said body, respectively, divergingly to
said periphery of said body for facilitating engagement of said
throughslot in said body with the engaged guitar strap peg of the
guitar.

007729-0450